

COMBINED CULTIVATOR FINISHER

- The machine combines several working operations in one pass: shallow cultivation, deep tillage, subsequent levelling and soil consolidation
- Non-stop hydropneumatic protection against tine overloading
- Working depth up to 35 cm, hydraulically adjustable by adjusting the drawbar and rear support roller
- Maximum material throughput by arranging tines into 3 rows and extending the row spacing
- Integrated axle for better manoeuvrability and even load during work
- Wide range of support rollers: tubular, DDL, Cracker, U-roller and double U-roller
- Robust frame made of high-strength materials
- Easy maintenance due to minimal lubrication points



Frame

Semi-carried, hydraulically folded (models 400 and 520)



Working width

3, 4.15 and 5.4 m



Working speed

up to 10 km/h



Working depth

up to 35 cm



Disc diameter

510 mm



Tines protection

Non-stop hydropneumatic



Application

shallow and deep tillage

TECHNICAL DATA

		300	400	520
Working width	[cm]	300	415	540
Transport width	[cm]	300	280	280
Min. tractor power	[HP]	190	240	300
Number of discs / diameter of discs	[mm]	22 / 510	32 / 510	44 / 510
Number of tines / tines spacing	[mm]	9 / 325	13 / 310	17 / 310
Number of levelling discs / pens		8	10	12
Max. working depth	[cm]	35	35	35
Axle tyre dimension		19/45-17	550/45-22,5	550/45-22,5
Weight	[kg]	3300 - 4000	4900 - 5700	5600 - 6500
Working speed	[km/h]	6-10	6-10	6-10
Connection (standard)		swivel eye 51 mm		

WWW.SMSCZ.CZ

SMS CZ s. r. o. / U Saské brány 12, Rokycany, 337 01 / smscz@smscz.cz / +420 371 722 137

f @smscz.machinery

@smscz_machinery



Funded by
the European Union