

MACHINE ADVANTAGES

- Discs are mounted on the frame using high-strength double tines, increasing the rigidity and flexibility of the entire working assembly
- The disc working angle ensures aggressive engagement and excellent performance even at higher speeds
- High ground clearance and wide spacing between working sections prevent clogging
- Option to choose disc size – 510 mm as standard, 560 mm available on request
- Wide range of accessories (support rollers, seeding attachments, and more)
- Hydraulically adjustable working depth

APPLICATIONS

- Fast shallow stubble cultivation up to 12 cm deep
- Intensive mixing of crop residues
- Seedbed preparation after ploughing or loosening
- Uniform incorporation of organic matter
- Soil reconsolidation and restoration of capillarity
- Option to equip with a seeding device for sowing cover crops and green manure



SUPPORT ROLLERS



Tube roller
ø 540 mm
Suitable for standard conditions



U roller
ø 540 mm
Excellent crumbling effect



Spring roller
ø 530 mm
High resistance to sticking



DDL roller
ø 560 mm
Excellent crushing and compacting effect



Type
Carried,
hydraulically foldable



Working width
4 - 6 m



Working depth
Up to 12 cm



Disc diameter
510 mm
or 560 (option)

| TECHNICAL DATA | 400 | 500 | 600 |
|----------------------------|---------------------------------|---------|---------|
| Type | Carried, hydraulically foldable | | |
| No. of frames | 2 | | |
| Working width [cm] | 430 | 510 | 600 |
| Transport width [cm] | 255 | | |
| Number of discs [pcs] | 32 | 40 | 48 |
| Min. tractor power [kW/HP] | 110/150 | 140/180 | 170/230 |
| Weight* [kg] | 2600 | 3000 | 3400 |
| Connection (standard) | cat. 3N | | |

*According to the selected specification.

DISC TYPES



Standard
ø 510 mm
or ø 560 mm



Labrador
ø 510 mm

WWW.SMSCZ.CZ

SMS CZ s. r. o. / U Saské brány 12, Rokycany, 337 01 / smscz@smscz.cz / +420 371 722 137

@smscz.machinery

@smscz_machinery



Funded by
the European Union