

Machine Advantages

- Pneumatic seed drill
- Robust machine construction ensures reliable operation even in heavy and stony soils
- Slit seeding technology ensures high germination rates
- Suitable for small to medium-sized farms

Applications

- Ideal for establishing and overseeding permanent grasslands
- Suitable for sowing most common field crops
- Levels small surface irregularities and consolidates the soil with a roller
- Removes old vegetation and moss
- Restores soil capillarity > uniform plant emergence even during dry periods
- No damage to turf or pulling stones to the surface
- An alternative to complete grassland renewal with lower energy requirements
- Also suitable for erosion-prone land

TESTED
Landwirt



Type
Carried



Working width
2.5 and 3 m



Working speed
up to 12 km/h



Application
in seeding and restoration of meadows and pastures.

PACKER ROLLERS



Ring Z

- ø 510/530 mm,
- Material: GGG 50 ductile iron
- Suitable for grassland application



Ring D

- ø 540/570 mm,
- Material: GGG 50 ductile iron
- Suitable for field application

SEEDING UNIT

- Electric or hydraulic fan drive
- Various types of control modules
- Available hopper capacities: 300 – 800 l

HARROW

- Single row of 12 mm spring tines

| TECHNICAL DATA | | 250 | 300 |
|-------------------------|---------|-------------|-------------|
| Working width | [cm] | 250 | 300 |
| Transport width | [cm] | 250 | 300 |
| Weight | [kg] | 1 900-2 500 | 2 100-2 700 |
| Min. power requirement | [kW/HP] | 75/100 | 85/110 |
| Working speed | [km/h] | 6- 12 | |
| Hopper capacity | [l] | 300-800 | |
| Hitch category | | cat. II | III/II |
| Number of seeding units | | 20 | 24 |
| Row spacing | [mm] | 125 | |
| Working depth | [cm] | up to 10 | |

WWW.SMSCZ.CZ

SMS CZ s. r. o. / U Saské brány 12, Rokycany, 337 01 / smscz@smscz.cz / +420 371 722 137

f @smscz.machinery

ig @smscz_machinery



Funded by
the European Union